

VNIV.EX6430 - SPRINKLERS, AUTOMATIC AND OPEN

Sprinklers, Automatic and Open

See General Information for Sprinklers, Automatic and Open

NANJING TUNA FIRE PROTECTION CO LTD

EX6430

599 ZHUSHAN RD

JIANGNING DISTRICT

NANJING, JIANGSU 211112 CHINA

Sprinkler Identification Number (SIN), Glass Bulb Type NX001, NX002, NX003, NX004, NX005, NX006, NX007, NX008, NX017, and NX018.

UPRIGHT AND PENDENT STANDARD SPRAY SPRINKLERS NOMINAL 5.6 K - FACTOR

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
NX003	SR	Upright	5.6	175	135, 155, 175, 200
NX004	QR	Upright	5.6	175	135, 155, 175, 200
NX005	SR	Pendent	5.6	175	135, 155, 175, 200
NX006	QR	Pendent	5.6	175	135, 155, 175, 200

STANDARD SIDEWALL SPRAY SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	System Working Pressure, psig	Temp Rating, °F
NX001+#	SR	Horizontal	5.6	175	135, 155, 175, 200
NX002+#	QR	Horizontal	5.6	175	135, 155, 175, 200
NX017*#	SR	Horizontal	5.6	175	135, 155, 175, 200
NX018*#	QR	Horizontal	5.6	175	135, 155, 175, 200

+ - Installed 4 to 12 in. below ceiling.

* - Installed 4 to 6 in. below ceiling.

- For ordinary hazard occupancies.

FLUSH, RECESSED, AND CONCEALED SPRINKLERS

SIN	Response Type	Type	Nom K-Factor	Temp. Rating, °F	
				Cover	Sprinkler
NX007	SR	Concealed	5.6	135, 155	135, 155, 175, 200
NX008	QR	Concealed	5.6	135, 155	135, 155, 175, 200

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"